



Thin Client Technology At Its Peak

Part Number: 5470 **5470** thin client Value Class Thin Client

The 5470 is an affordable, energy efficient, compact thin client. Assembled in the UK, this unit weighs just over 1lb. allowing flexible mounting options and low shipping costs. The 5470 has no moving parts and consumes only 8 to 9 watts of energy.



CE.Net Operating System	Centralised Management
Small Form Factor for Space-Saving	1600 X1200 Maximum Resolution
Read Only File System	Vide Screen Support
VIE6 CE Version Browser	Built-in Kensington Security
Supports RDP, ICA and VDI Deployment	VRoHS Compliant
V Energy Efficient (Only 8-9W)	🧹 Energy Star Compliant
TN5250e/TN3270e sessions, Telnet with SSH, SSL, Wyse 60, xTerm R6, VT100, VT200 and VT400	VESA Mounting Capability

Reduce IT Costs, Increase Security and Improve Efficiency by Switching to 10ZiG Thin Clients







5470 thin client



System		
Operating System	CE.Net 5.0	
Form Factor	Compact case	
Management	10ZiG Management Software	
Processor	VIA Eden 500MHz	
Video Resolution	Up to 1600 x 1200 x 32 bit color	
Wide Screen Support		•
Memory		
RAM (Stand/MAX)	256MB/1GB	
Storage (Stand/MAX)	128MB/128MB	
Software Configu	iration	
ICA	Version 9	
RDP	5.5	
Client Software	Propalms	
VDI Clients	Optional Quest v Leostream, Erico WebConnect, VM PCoIP and 2X V	om PowerTerm
		•
Dimensions		
Dimensions Device	1.4" W x 6.1" H x 36mm x 156 mm	x 4.8" D
		x 4.8" D n x 122 mm
Device	36mm x 156 mm	x 4.8" D n x 122 mm
Device Weight	36mm x 156 mm	x 4.8" D n x 122 mm
Device Weight Audio	36mm x 156 mm	x 4.8" D n x 122 mm
Device Weight Audio Mic In/Line Out	36mm x 156 mm	x 4.8" D n x 122 mm • x 1 (built-in 1W internal
Device Weight Audio Mic In/Line Out Speaker	36mm x 156 mm 1.7 lbs. (0.75kg)	x 4.8" D n x 122 mm • x 1 (built-in 1W internal
Device Weight Audio Mic In/Line Out Speaker Management	36mm x 156 mm 1.7 lbs. (0.75kg) er	x 4.8" D n x 122 mm • x 1 (built-in 1W internal
Device Weight Audio Mic In/Line Out Speaker Management 10ZiG Remote Manag	36mm x 156 mm 1.7 lbs. (0.75kg) er Configurations	x 4.8" D n x 122 mm • x 1 (built-in 1W internal
Device Weight Audio Mic In/Line Out Speaker Management 10ZiG Remote Manag Various Client	36mm x 156 mm 1.7 lbs. (0.75kg) er Configurations nals	x 4.8" D n x 122 mm • x 1 (built-in 1W internal
Device Weight Audio Mic In/Line Out Speaker Management 10ZiG Remote Manag Various Client Shadow Termin	36mm x 156 mm 1.7 lbs. (0.75kg) er Configurations nals on off, Reboot	x 4.8" D n x 122 mm • x 1 (built-in 1W internal
Device Weight Audio Mic In/Line Out Speaker Management 10ZiG Remote Manag Various Client Shadow Termin Status Indicatio Power on, Log	36mm x 156 mm 1.7 lbs. (0.75kg) er Configurations nals on off, Reboot	x 4.8" D n x 122 mm • x 1 (built-in 1W internal
Device Weight Audio Mic In/Line Out Speaker Management 10ZiG Remote Manage Various Client Shadow Termin Status Indicatio Power on, Log and Shut down	36mm x 156 mm 1.7 lbs. (0.75kg) er Configurations nals on off, Reboot	x 4.8" D n x 122 mm • x 1 (built-in 1W internal
Device Weight Audio Mic In/Line Out Speaker Management 10ZiG Remote Manag Various Client Shadow Termi Status Indicatio Power on, Log and Shut down Task Scheduler	36mm x 156 mm 1.7 lbs. (0.75kg) 1.7 lbs. (0.75kg) er Configurations nals on off, Reboot	x 4.8" D n x 122 mm • x 1 (built-in 1W internal

Ports	
USB Ports Type 2	x4
PS2 Port	A-+
	•
Environmental	ure 0° ~ 35°C
Operating Temperat	arc .
On exeting I humidity	32° ~ 95°F 20% ~ 80% non-condensing
Operating Humidity	20% 00% hon-condensing
Power	
Consumption	8 - 9 watts average
AC/DC Adapter	Included
Networking	
	Autosensing, 10/100 Ethernet, RJ-45, WakeOnLAN, PXE boot, Internal 802.11 b/g/n wireless option
Compliance	
	RoHS
	WEEE
	CE
	FCC
	Energy Star Compliant
Features	
Security Features	Kensington Security Lock Slot
	Auto start/auto-restart connection Lock-down user interface
Language Support	US, UK English, German,
	French, Swedish and others by request
Ordering Informa	request
	request
Ordering Informa PID Description	request tion E.Net, RDP, ICA,TN5250e, TN3270e
Ordering Informa PID Description 5470 RBT-470, C	request tion E.Net, RDP, ICA,TN5250e, TN3270e Mouse
OrderingInformationPIDDescription5470RBT-470, C and Optical9001USB to Cer	request tion E.Net, RDP, ICA,TN5250e, TN3270e Mouse
OrderingInformationPIDDescription5470RBT-470, C and Optical9001USB to Cer9004VESA Mourt	request tion E.Net, RDP, ICA,TN5250e, TN3270e Mouse htronics
OrderingInformationPIDDescription5470RBT-470, C and Optical9001USB to Cer9004VESA Mour9010Internal Wir	request tion E.Net, RDP, ICA, TN5250e, TN3270e Mouse htronics nting Bracket (with short VGA cable)

