



Thin Client Technology At Its Peak

Part Number: 5617v

5617v thin client Performance Class Thin Client

The 5617v Thin Client is designed for a desktop virtualisation (VDI) environment. Available with a choice of VMware View with PCoIP, Citrix XenDesktop, or Quest vWorkspace, this unit offers a complete desktop experience.

The 5617v is the fastest, small form factor thin client on the market. This energy efficient unit boasts the Intel Atom N270 1.6 GHz Dual Thread processor offering exceptional performance and flexibility.



Windows Embedded Standard 7	Centralised Management
Small Form Factor for Space-Saving	Optional Internal 802.11 b/g/n Wireless with WEP, WPA, WPA2 and Cisco Compliant
Multiple Level Lock Down Feature with Protect File System	✓ Wide Screen Support
✓ IE8	1920 X1200 Maximum Resolution
Supports RDP 7, ICA and VDI Deployment	→ Built-in Kensington Security Lock
Energy Efficient (only 12 Watts)	RoHS Compliant
Designed for Virtual Desktop Deployment	Energy Star Compliant
VESA Mounting Capability	Jual Monitor Option

Reduce IT Costs,
Increase Security
and Improve
Efficiency by
Switching to 10ZiG
Thin Clients







5617v thin client



System		
Operating System	Window Embedded Standard 7	
Form Factor	Compact case	
Management	10ZiG Management Software	
Processor	Intel Atom N270 1.6GHz Dual Thread	
Browser	IE8	
Video Resolution	Up to 1920 x 1200	
Wide Screen Support	•	
Dual Monitor	Optional	
Memory		
RAVI (Stand/MAX)	1GB/2GB	
Storage (Stand/MAX)	4GB/16GB	
Software Configu	ration	
ICA	Version 12.1 with HDX	
RDP	7	
Client Software	Windows Media Player	
	Adobe Flash Player	
	Shockwave	
	Sun JVM & MS Java	
	VNC Shadowing	
	ThinPrint.print	
VDI Client	Choice one of the following (please specify your preference when ordering:) Quest vWorkspace, Citrix XenDesktop, and VMware View with PCoIP. * Other VDI clients are available upon request.	
Dimensions		
Device	1.4" W x 6.1" H x 4.8" D 36mm x 156 mm x 122 mm	
Weight	1.7 lbs. (0.75kg)	
Audio		
Mic In/Line Out	•	
Speaker	x 1 (built-in 1W internal Speaker)	
Management		
10ZiG Remote Manage	er •	
Various Client Configurations ●		
Shadow Termin		
Status Indication •		
Power on, Log off, Reboot and Shut down		
Task Scheduler	•	

Cloning of Terminals

Group Operations

Recover Image

Update of Firmware

Ports		
USB Por	rts Type 2	x4
PS2 Por	t	•
Enviro	nmental	
Operati	ng Temperature	0° ~ 35°C
		32° ~ 95°F
Operati	ng Humidity	20% ~ 80% non-condensing
Power		
Consum	ption	12 watts average
AC/DC	Adapter	Included
Netwo	rking	
		Autosensing, 10/100/1000 Ethernet, RJ-45, WakeOnLAN, PXE boot, Internal 802.11 b/g/n wireless option
Compli	iance	
		RoHS
		WEEE
		CE FCC
		Energy Star Compliant
Feature	es	
Security	Features	Kensington Security Lock Slot
		Auto start/auto-restart connection, Multiple level lock-down user interface
		Administrative and user passwords
Languag	e Support	US, UK English, German, French, and others by request
Orderir	ng Information	
PID	Description	
5617v	5617v, WES7, IE8, RDP, ICA, Flash Player, Shockwave, Windows Media Player 12, Sun JVM & MS Java, VDI Clients and Optical Mouse	
5616v	5616v, WES (XPe SP3), IE8, RDP, ICA, Flash Player, Shockwave, Windows Media Player, Sun JVM & MS Java, VDI Clients and Optical Mouse	
9001	USB to Centronics	
9006A	VESA Mounting Bi	racket (with DVI - DVI cable)
9006B	VESA Mounting Bracket (with DVI - VGA cable)	
9007	Dual Monitor Option	
9010	Internal Wireless (802.11 b/g/n + Cisco)	
8104b	104-Key PC Keyboard	













