



Thin Client Technology At Its Peak

Part Number: 5672v

5672v thin client Performance Class Thin Client

The 5672v Thin Client is designed for a desktop virtualisation (VDI) environment. Complete with VMware View with PCoIP, Citrix XenDesktop, 2X VirtualDesktopServer, Quest vWorkspace, Leostream Connection Broker, Ericom PowerTermWebConnect and Kaviza VDI-In-A-Box, this unit offers a complete desktop experience.

The 5672v is the fastest, small form factor thin client on the market. This energy efficient unit boasts the Intel Atom N270 1.6 GHz Dual Thread processor offering exceptional performance and flexibility. The 5672v also offers Fast Boot for half the normal boot up time.



The **5672v** supports three modes of operation:

Desktop Mode	Windows 7 type user interface provides access to all applications in a windowing environment.	
WBT Mode	Windows based Terminal mode, where the terminal behaves like a CE.NET device with full screen applications, Terminal Server access, Citrix or VDI which auto start and auto-reconnect.	
Kiosk Mode	Dedicated Kiosk type of interface not configurable by the user of the terminal.	

Reduce IT Costs, Increase Security and Improve Efficiency by switching to 10ZiG Thin Clients

Linux Operating System	Centralised Management Utility
Small Form Factor for Space-Saving	Optional Internal 802.11 b/g/n Wireless with WEP, WPA, WPA2 Personal/Enterprise
Read Only File System	✓ Wide Screen Support
Embedded Firefox Browser	1920 X1200 Maximum Resolution
Supports RDP, ICA and VDI Deployment	Built-in Kensington Security Lock
Energy Efficient (only 12 Watts)	RoHS & Energy Star Compliant
Designed for Virtual Desktop Deployment	Jual Monitor Option
VESA Mounting Capability	✓ Cisco VPN







5672v thin client



System		
Operating System	Linux 2.6 Kernel	
Form Factor	Compact case	
Management	10ZiG Management Software	
Processor	Intel Atom N270 1.6 GHz Dual Thread	
Browser	Firefox 3.0	
Video Resolution	Up to 1920 x 1200 X 32 bit color	
Wide Screen Support	•	
Dual Monitor	Optional	
Memory		
RAM (Stand/MAX)	512MB/2GB	
Storage (Stand/MAX)	512MB/2GB	
Software Configuration		
ICA	Version 11	
ICA RDesktop	Version 11 1.6	
1000		
RDesktop	1.6	
RDesktop	1.6 Adobe Flash Player	
RDesktop	1.6 Adobe Flash Player Sun JVM	
RDesktop	1.6 Adobe Flash Player Sun JVM VNC Shadowing	
RDesktop	1.6 Adobe Flash Player Sun JVM VNC Shadowing Cisco VPN	
RDesktop	1.6 Adobe Flash Player Sun JVM VNC Shadowing Cisco VPN Linux PN Agent	

Dimensions		
Device	1.4" W x 6.1" 36mm x 156	H x 4.8" D mm x 122 mm
Weight	1.7 lbs. (0.75	kg)
Audio		
Mic In/Line Out		1 each
Speaker		x 1 (built-in 1W internal Speaker)
Management		Supported
10ZiG Remote Man	ager	•
Various Client Configurations		•
Shadow Terminals		•
Status Indication •		•
Power on, Log off, Reboot and Shut down		•
Task Scheduler		•
Cloning of Terminals		•
Group Operations		•
Update of Firmware		•

Ports		
USB Ports Type 2	x4	
DVI Port	x1	
PS2 Port	x1	
Environmental		
Operating Temperature	0° ~ 35°C	
	32° ~ 95°F	
Operating Humidity	20% ~ 80% non-condensing	
Power		
Consumption	12 watts average	
AC/DC Adapter	Included	
Networking		
	Autosensing, 10/100/1000 Ethernet, RJ-45, WakeOnLAN, PXE boot,Internal 802.11 b/g/n wireless option	
Compliance		
	RoHS	
	WEEE	
	CE	
	FCC	
	Energy Star Compliant	
Features		
Security Features	Kensington Security Lock Slot Auto start/auto-restart connection Lock-down user interface	
Language Support	UK, US English, German, French, Swedish and others by request	

Orderi	ng Information
PID	Description
5672v	5672v, Linux, Firefox Browser, RDesktop, ICA, VDI Clients and Optical Mouse
9001	USB to Centronics
9006A	VESA Mounting Bracket (with DVI - DVI cable)
9006B	VESA Mounting Bracket (with DVI - VGA cable)
9007	Dual Monitor Option (1x DVI/1x VGA)
9010	Internal Wireless (b/g/n)
8104b	104-Key PC Keyboard
9008	DVI to VGA Adapter

