



Thin Client Technology At Its Peak

Part Number: 6716

6716 thin client Elite Class Thin Client

The 6716 offers a combination of high performance and expandability. Powered by a VIA Nano processor, this unit is powerful, energy efficient and secure.

Designed for easy expansion and capable of dual monitors and rich multi-media graphics, the 6716 provides a superior end user experience.



✓ XPe Operating System	Centralised Management
✓ No Moving Parts	Optional Internal 802.11 b/g/n Wireless with WEP, WPA, WPA2 and Cisco Compliant
Multiple Level Lock Down Feature with Protected File System	✓ Wide Screen Support
IE6 (*7/8 available upon request)	1920 x 1080 Maximum Resolution
Supports RDP, ICA and VDI Deployment	Built-in Kensington Security Lock
Energy Efficient	Dual and Quad Monitor Support
BOSaNOVA Secure 5250 Terminal Emulation	WES (XPe SP3) available upon request

Reduce IT Costs, Increase Security and Improve Efficiency by Switching to 10ZiG Thin Clients







6716 thin client



System		
Operating System	XPe SP2 (WES (XPe SP3) 2009	
Operating System	available upon request)	
Form Factor	Compact case	
Management	10ZiG Management Software	
Processor	VIA Nano 1.3 GHz	
Browser	IE6 (**7 or 8 available upon request)	
Video Resolution	Up to 1920 x 1080 x 32 bit color	
Wide Screen Support	• 1020 X 1000 X 02 5K 00101	
Wide Screen Support	·	
Monitor Support	Dual and Monitor Support optional	
Memory		
RAVI (Stand/MAX)	512MB/2GB	
Storage (Stand/MAX)	512MB/16GB	
Software Configu		
Host Access	a de l'on	
(BOSaNOVA Secure)	Supports TN5250e, SSL and SSO	
ICA	Version 12.1 with HDX	
RDP	6.1 (RDP 7 available on WES)	
Client Software	Adobe Acrobat Viewer	
	Adobe Flash Player	
	MS Office Viewers	
	Microsoft Outlook Express	
	Windows Media Player	
	Shockwave	
	Sun JVM & MS Java	
VDI Clients	VNC Shadowing Optional Quest vWorkspace, Leostream, Citrix XenDesktop, Ericom PowerTerm WebConnect, VMware View with PCoIP and 2X VirtualDesktopServer	
	VNC Shadowing Optional Quest vWorkspace, Leostream, Citrix XenDesktop, Ericom PowerTerm WebConnect, VMware View with PCoIP	
VDI Clients Dimensions Device	VNC Shadowing Optional Quest vWorkspace, Leostream, Citrix XenDesktop, Ericom PowerTerm WebConnect, VMware View with PCoIP	
Dimensions	VNC Shadowing Optional Quest vWorkspace, Leostream, Citrix XenDesktop, Ericom PowerTerm WebConnect, VMware View with PCoIP and 2X VirtualDesktopServer	
Dimensions	VNC Shadowing Optional Quest vWorkspace, Leostream, Citrix XenDesktop, Ericom PowerTerm WebConnect, VMware View with PCoIP and 2X VirtualDesktopServer 2.2" W x 9" H x 8.2" L	
Dimensions Device	VNC Shadowing Optional Quest vWorkspace, Leostream, Citrix XenDesktop, Ericom PowerTerm WebConnect, VMware View with PCoIP and 2X VirtualDesktopServer 2.2" W x 9" H x 8.2" L 57 mm x 230 mm x 210 mm	
Dimensions Device Weight	VNC Shadowing Optional Quest vWorkspace, Leostream, Citrix XenDesktop, Ericom PowerTerm WebConnect, VMware View with PCoIP and 2X VirtualDesktopServer 2.2" W x 9" H x 8.2" L 57 mm x 230 mm x 210 mm	
Dimensions Device Weight Audio	VNC Shadowing Optional Quest vWorkspace, Leostream, Citrix XenDesktop, Ericom PowerTerm WebConnect, VMware View with PCoIP and 2X VirtualDesktopServer 2.2" W x 9" H x 8.2" L 57 mm x 230 mm x 210 mm	
Dimensions Device Weight Audio Mic In/Line Out Speaker	VNC Shadowing Optional Quest vWorkspace, Leostream, Citrix XenDesktop, Ericom PowerTerm WebConnect, VMware View with PCoIP and 2X VirtualDesktopServer 2.2" W x 9" H x 8.2" L 57 mm x 230 mm x 210 mm 3.7 lbs. (1.7kg) • x 1 (built-in 1W internal	
Dimensions Device Weight Audio Mic In/Line Out Speaker Management	VNC Shadowing Optional Quest vWorkspace, Leostream, Citrix XenDesktop, Ericom PowerTerm WebConnect, VMware View with PCoIP and 2X VirtualDesktopServer 2.2" W x 9" H x 8.2" L 57 mm x 230 mm x 210 mm 3.7 lbs. (1.7kg) • x 1 (built-in 1W internal Speaker)	
Dimensions Device Weight Audio Mic In/Line Out Speaker Management 10ZiG Remote Manage	VNC Shadowing Optional Quest vWorkspace, Leostream, Citrix XenDesktop, Ericom PowerTerm WebConnect, VMware View with PCoIP and 2X VirtualDesktopServer 2.2" W x 9" H x 8.2" L 57 mm x 230 mm x 210 mm 3.7 lbs. (1.7kg)	
Dimensions Device Weight Audio Mic In/Line Out Speaker Management 10ZiG Remote Manage Various Client	VNC Shadowing Optional Quest vWorkspace, Leostream, Citrix XenDesktop, Ericom PowerTerm WebConnect, VMware View with PCoIP and 2X VirtualDesktopServer 2.2" W x 9" H x 8.2" L 57 mm x 230 mm x 210 mm 3.7 lbs. (1.7kg)	
Dimensions Device Weight Audio Mic In/Line Out Speaker Management 10ZiG Remote Management Shadow Termin	VNC Shadowing Optional Quest vWorkspace, Leostream, Citrix XenDesktop, Ericom PowerTerm WebConnect, VMware View with PCoIP and 2X VirtualDesktopServer 2.2" W x 9" H x 8.2" L 57 mm x 230 mm x 210 mm 3.7 lbs. (1.7kg)	
Dimensions Device Weight Audio Mic In/Line Out Speaker Management 10ZiG Remote Manage Various Client of Shadow Termine Status Indication	VNC Shadowing Optional Quest vWorkspace, Leostream, Citrix XenDesktop, Ericom PowerTerm WebConnect, VMware View with PCoIP and 2X VirtualDesktopServer 2.2" W x 9" H x 8.2" L 57 mm x 230 mm x 210 mm 3.7 lbs. (1.7kg)	
Dimensions Device Weight Audio Mic In/Line Out Speaker Management 10ZiG Remote Management Shadow Termin	VNC Shadowing Optional Quest vWorkspace, Leostream, Citrix XenDesktop, Ericom PowerTerm WebConnect, VMware View with PCoIP and 2X VirtualDesktopServer 2.2" W x 9" H x 8.2" L 57 mm x 230 mm x 210 mm 3.7 lbs. (1.7kg)	
Dimensions Device Weight Audio Mic In/Line Out Speaker Management 10ZiG Remote Manage Various Client of Shadow Termine Status Indication Power on, Log	VNC Shadowing Optional Quest vWorkspace, Leostream, Citrix XenDesktop, Ericom PowerTerm WebConnect, VMware View with PCoIP and 2X VirtualDesktopServer 2.2" W x 9" H x 8.2" L 57 mm x 230 mm x 210 mm 3.7 lbs. (1.7kg)	
Dimensions Device Weight Audio Mic In/Line Out Speaker Management 10ZiG Remote Manage Various Client Shadow Termin Status Indication Power on, Logand Shut down	VNC Shadowing Optional Quest vWorkspace, Leostream, Citrix XenDesktop, Ericom PowerTerm WebConnect, VMware View with PCoIP and 2X VirtualDesktopServer 2.2" W x 9" H x 8.2" L 57 mm x 230 mm x 210 mm 3.7 lbs. (1.7kg) x 1 (built-in 1W internal Speaker) ger Configurations als on off, Reboot	
Dimensions Device Weight Audio Mic In/Line Out Speaker Management 10ZiG Remote Manage Various Client Shadow Termin Status Indication Power on, Log and Shut down Task Scheduler	VNC Shadowing Optional Quest vWorkspace, Leostream, Citrix XenDesktop, Ericom PowerTerm WebConnect, VMware View with PCoIP and 2X VirtualDesktopServer 2.2" W x 9" H x 8.2" L 57 mm x 230 mm x 210 mm 3.7 lbs. (1.7kg)	
Dimensions Device Weight Audio Mic In/Line Out Speaker Management 10ZiG Remote Manage Various Client Shadow Termin Status Indication Power on, Log and Shut down Task Scheduler Cloning of Termin	VNC Shadowing Optional Quest vWorkspace, Leostream, Citrix XenDesktop, Ericom PowerTerm WebConnect, VMware View with PCoIP and 2X VirtualDesktopServer 2.2" W x 9" H x 8.2" L 57 mm x 230 mm x 210 mm 3.7 lbs. (1.7kg)	
Dimensions Device Weight Audio Mic In/Line Out Speaker Management 10ZiG Remote Manage Various Client Shadow Termin Status Indication Power on, Log and Shut down Task Scheduler Cloning of Termin Group Operation	Optional Quest vWorkspace, Leostream, Citrix XenDesktop, Ericom PowerTerm WebConnect, VMware View with PCoIP and 2X VirtualDesktopServer 2.2" W x 9" H x 8.2" L 57 mm x 230 mm x 210 mm 3.7 lbs. (1.7kg)	
Dimensions Device Weight Audio Mic In/Line Out Speaker Management 10ZiG Remote Manage Various Client of Shadow Termin Status Indication Power on, Log and Shut down Task Scheduler Cloning of Term Group Operation Update of Firm Recover Image Configuration of	VNC Shadowing Optional Quest vWorkspace, Leostream, Citrix XenDesktop, Ericom PowerTerm WebConnect, VMware View with PCoIP and 2X VirtualDesktopServer 2.2" W x 9" H x 8.2" L 57 mm x 230 mm x 210 mm 3.7 lbs. (1.7kg)	

Ports		
USB Port	s Type 2	6
PS2 Port		x2
Serial Por	-	1
Parallel P	ort	1***
Video Po	rts	2 x DVI
Environ	mental	
Operating	g Temperature	0° ~ 40°C
·	•	32° ~ 104°F
Operating	Humidity	20% ~ 90% non-condensing
Power		
Consump		14 watts average
AC/DC A	dapter	Included
Networ	king	
		Autosensing, 10/100/1000 Ethernet, RJ-45, WakeOnLAN, PXE boot, Internal 802.11 b/g/n wireless option.
Complia	ance	
		RoHS
		WEEE
		CE FCC
Feature	S	1 00
Security		Kensington Security Lock Slot
,		Auto start/auto-restart connection, Multiple level lock-down user interface
		Administrative and user passwords
Language	Support	US, UK English, German, French, Swedish and others by request
Orderin	g Informatio	n
PID	Description	
6716NE	6716, XPe, IE6 SP3, Sun JVM & MS Java, RCP, ICA, Shockwave, Flashplayer, Optical Mouse, Adob Acrobat Viewer, MS Office Viewers, MS Outlook Express and Windows Media Player.	
6716	Featured software from 6716NE plus BOSaNOVA Secure Emulation	
9001	USB to Centro	nics
9011	PCI Expansion	n Card (Serial and Parallel Port)
9010	Internal Wirele	ss (802.11 b/g/n + Cisco)
8122b	122-Key Drive	rless PC Keyboard
8104b	104-Key PC K	eyboard
8008	1 GB DOM (Call for Customization and other Embedded Applications)	
8010	Quad video su GB DOM	upport includes DVI & VGA ports & 1
** Require	IE / Or 8, Sun J	VM 1.6, Adobe 8 or 9 (IE 8 available on WES)







*VT320, VT420, VT52, WYSE60, WYSE60/AIF, VAX/AIX, LINUX, HP70094/8, HP70092/6, HP2392A *** One parallel and one serial port available with optional PCI card (9011)



